

What is claimed is:

1. A method of protecting a vehicle license plate by a protector and a holder with pressed or expanded function comprising to screw or push the protector through the hole on a vehicle  
5 license plate and into the holder on a vehicle body to hold the protector, plate and holder together after the pressed or expanded part reruns for protecting the plate from being stolen.
2. The method of claim 1 wherein the holder on a vehicle body is the existing hole or screw holder on a vehicle body.
- 10 3. The method of claim 2 wherein the existing screw holder on a vehicle body has a function to be expanded.
4. The method of claim 1 wherein the protector has three parts of top part, middle part and  
15 bottom part.
5. The method of claim 4 wherein the top is screw, the middle part has a smaller diameter compared with the internal diameter of the holder and longer length than the length of the holder, and the bottom part has a larger diameter compared with the internal diameter of the  
20 holder.
6. The method of claim 4 wherein the bottom part with or without cuts has the reducing diameter to the bottom end gradually.
- 25 7. The method of claim 1 wherein the protector is not removed from the holder without releasing the connection between the protector and holder.
8. A product for protecting a vehicle license plate according to the method of claims 1.
- 30 9. A method of protecting a plate by a protector and a holder with pressed or expanded function comprising to screw or push the protector through the hole on a plate and into the holder on a support body to hold the protector, plate and holder together after the pressed

or expanded part reruns for protecting the plate from being stolen.

10. The method of claim 9 wherein the holder on a support body is a hole or screw holder on the support body.

5

11. The method of claim 9 wherein the screw holder has the function to be expanded.

12. The method of claim 9 wherein the protector has three parts of top part, middle part and bottom part.

10

13. The method of claim 12 wherein the top is screw, the middle part has a smaller diameter compared with the internal diameter of the holder and longer length than the length of the holder, and the bottom part has a larger diameter compared with the internal diameter of the holder.

15

14. The method of claim 12 wherein the bottom part with or without cuts has the reducing diameter to the bottom end gradually.

20

15. The method of claim 9 wherein the protector is not removed from the holder without releasing the connection between the protector and the holder.

16. A product for protecting a plate according to the method of claim 9.

25

30

35